

In the claims:

1. An improved centrifugal impeller for use in low profile heat sinks and the like having a multiplicity of small upright spaced apart heat dissipating elements in an array defining a multiplicity of small airflow passageways therebetween with a cavity located centrally therewithin, the impeller being adapted to be disposed adjacent to and about the array of heat dissipating elements and to be driven by an electric motor disposed in the central cavity, and the impeller being open radially inwardly for radial communication with the air flow passageways between the heat dissipating elements and at least partially open radially outwardly for the discharge of spent cooling air, the impeller also having a radially extending backplate which is exposed upwardly and which defines an inlet opening for the axial downward flow of cooling air, and a plurality of rearwardly curved air moving blades forming a part of the impeller and serving to effect a right angle turn in air flow direction and to withdraw air radially outwardly from the passageways between the heat dissipating elements and direct the same radially outwardly.

2. An improved centrifugal impeller as set forth in claim 1 wherein the ratio of the radial dimension  $W$  to the overall radius  $R$  of the impeller falls in the range 0.25 to 0.5.

3. An improved centrifugal impeller as set forth in claim 1 wherein the ratio of radial dimension  $W$  to the overall radius  $R$  of the impeller falls in the range 0.31 to 0.37.

4. An improved centrifugal impeller as set forth in claim 1 wherein the impeller has between 20 and 26 blades.

5. An improved centrifugal impeller as set forth in claim 4 wherein the ratio of radial dimension W to the overall radius R of the impeller falls in the range 0.31 to 0.37.

6. An improved centrifugal impeller as set forth in claim 1 wherein the impeller blades each have an inlet angle in the range of  $28^{\circ}$  to  $40^{\circ}$  measured between a line tangent to a circle intersecting the inner blade edges and a line tangent to the blade centerline at its leading edge.

7. An improved centrifugal impeller as set forth in claim 1 wherein the impeller blades each have an inlet angle in the range of  $32^{\circ}$  to  $36^{\circ}$  measured between a line tangent to a circle intersecting the inner blade edges and a line tangent to the blade centerline at its leading edge.

8. An improved centrifugal impeller as set forth in claim 1 wherein the impeller blades each have a discharge angle in the range of  $32^{\circ}$  to  $44^{\circ}$  measured between a line tangent to the impeller periphery and a line tangent to the blade centerline at its trailing edge.

9. An improved centrifugal impeller as set forth in claim 1 wherein the impeller blades each have a discharge angle in the range of  $36^{\circ}$  to  $40^{\circ}$  measured between a line tangent to the impeller periphery and a line tangent to the blade centerline at its trailing edge.

10. An improved centrifugal impeller as set forth in claim 1 wherein the ratio of the impeller radial dimension to the impeller overall radius  $R$  falls in the range 0.31 to 0.37, wherein the impeller has between 20 and 26 blades, wherein the impeller blades each have an inlet angle in the range of  $32^\circ$  to  $36^\circ$  measured between
- 5 a line tangent to a circle intersecting the inner blade edges and a line tangent to the blade centerline at its leading edge, and wherein the impeller blades each have a discharge angle in the range  $36^\circ$  to  $40^\circ$  measured between a line tangent to the impeller periphery and a line tangent to the blade centerline at its trailing edge.

10  
20  
30  
40  
50  
60  
70  
80  
90  
100  
110  
120  
130  
140  
150  
160  
170  
180  
190  
200  
210  
220  
230  
240  
250  
260  
270  
280  
290  
300  
310  
320  
330  
340  
350  
360  
370  
380  
390  
400  
410  
420  
430  
440  
450  
460  
470  
480  
490  
500  
510  
520  
530  
540  
550  
560  
570  
580  
590  
600  
610  
620  
630  
640  
650  
660  
670  
680  
690  
700  
710  
720  
730  
740  
750  
760  
770  
780  
790  
800  
810  
820  
830  
840  
850  
860  
870  
880  
890  
900  
910  
920  
930  
940  
950  
960  
970  
980  
990  
1000